

安装依赖包

```
yum install -y centos-release-scl devtoolset-4-gcc-c++ devtoolset-4-gcc cmake  
openssl-devel bison git gmock ncurses ncurses-* autoconf
```

创建账号

```
groupadd mysql && useradd -r -g mysql mysql  
wget http://mirror.cnop.net/alisql/AliSQL-5.6.32.zip && unzip AliSQL-5.6.32.zip && cd  
AliSQL-master
```

```
scl enable devtoolset-4 bash
```

```
mkdir source_downloads && cd source_downloads && wget  
http://mirror.cnop.net/gmock/gmock-1.6.0.zip && cd ..
```

编译：

```
cmake \  
-DCMAKE_INSTALL_PREFIX=/usr/local/alisql \  
-DMYSQL_UNIX_ADDR=/usr/local/alisql/mysql.sock \  
-DDEFAULT_CHARSET=utf8 \  
-DDEFAULT_COLLATION=utf8_general_ci \  
-DWITH_INNODB_STORAGE_ENGINE=1 \  
-DWITH_ARCHIVE_STORAGE_ENGINE=1 \  
-DWITH_BLACKHOLE_STORAGE_ENGINE=1 \  
-DMYSQL_DATADIR=/usr/local/alisql/data \  
-DMYSQL_TCP_PORT=3306 \  
-DENABLE_DOWNLOADS=1
```

安装：

```
make  
make install
```

```
chown -R mysql.mysql /usr/local/alisql/  
echo never > /sys/kernel/mm/transparent_hugepage/enabled
```

```
chmod +x ./scripts/mysql_install_db
```

```
./scripts/mysql_install_db --user=mysql --basedir=/usr/local/alisql --
datadir=/usr/local/alisql/data
```

```
vi /etc/my.cnf #加入以下内容
```

```
[client]
port      = 3306
socket     = /tmp/mysql.sock
```

```
[mysqld]
port = 3306
socket = /tmp/mysql.sock
datadir = /usr/local/alisql/data
skip-external-locking
key_buffer_size = 16M
max_allowed_packet = 10M
table_open_cache = 64
sort_buffer_size = 512K
net_buffer_length = 8K
read_buffer_size = 256K
read_rnd_buffer_size = 512K
myisam_sort_buffer_size = 8M
thread_cache_size = 8
query_cache_size = 8M
tmp_table_size = 16M
max_connections = 500
max_connect_errors = 100
open_files_limit = 65535
log-bin=mysql-bin
binlog_format=mixed
server-id = 1
expire_logs_days = 10
default_storage_engine = InnoDB
innodb_file_per_table = 1
innodb_data_home_dir = /usr/local/alisql/data
innodb_data_file_path = ibdata1:10M:autoextend
innodb_log_group_home_dir = /usr/local/alisql/data
```

```
innodb_buffer_pool_size = 16M  
innodb_additional_mem_pool_size = 2M  
innodb_log_file_size = 5M  
innodb_log_buffer_size = 8M  
innodb_flush_log_at_trx_commit = 1  
innodb_lock_wait_timeout = 50
```

```
cp support-files/mysql.server /etc/init.d/mysqld
```

环境变量配置：

```
vi /etc/profile #加入以下  
PATH=/usr/local/alisql/bin:/usr/local/alisql/lib:$PATH  
export PATH
```

```
source /etc/profile
```

软链接：

```
ln -s /usr/local/alisql/bin/mysql /usr/bin  
  
chmod +x /etc/init.d/mysqld  
service mysqld start  
chkconfig --level 35 mysqld on
```

```
netstat -tulnp | grep 3306  
mysql -u root -p      #默认root密码为空
```

```
[root@cnop alisql]# mysql -u root -p
Enter password:
Welcome to the MySQL monitor.  Commands end with ; or \g.
Your MySQL connection id is 1
Server version: 5.6.32 Source distribution
Copyright (c) 2000, 2016, Oracle and/or its
affiliates. Other names may be trademarks
of their respective owners.
Type 'help;' or '\h' for help. Type '\c' to
mysql>
```

#授权新密码

```
mysqladmin -uroot -p password 123456
```

#运行后按提示输入一次确定密码即可 (这里是123456)

```
[root@cnop alisql]# mysqladmin -uroot -p password 123456
Enter password:
Warning: Using a password on the command line interface can be insecure.
```

```
mysql -uroot -p      #重新登录
```

参考 https://yq.aliyun.com/articles/327239?utm_content=m_1000010411